

TECHNICAL DATA SHEET**en**

Name of product:

PVB - Lacquer 0208

Type of product:	Rapidly drying, non-yellowing clear varnish based on polyvinyl butyral.
Application:	Temporary metal protection, wood coating, concrete bonding or other specialized uses.
Properties:	Extremely fast-drying, hard and tough coating.
Solids:	16 weight % 13 vol. %
Pre-treatment:	The surface must be free of grease, oil and rust contaminants.

Application:

Method:	Recommended viscosity:	Thinner:
Conventional spraying	20 - 25 sec. DIN-cup 4 mm	0700-68013

Drying:

	Drying time	Film thickness - dry
Dust dry	15 minutes 20 °C	60 - 80 µm
Dry to touch	15 minutes 20 °C	60 - 80 µm

Recommended coating thickness:	Wet film: 115 µm Dry film: 15 µm
---------------------------------------	---

Coverage:	Theoretical: 9 m ² /ltr.
------------------	--

Storage:	Store cool and dry
-----------------	--------------------

Shelf-life:	24 Months in an unopened container
--------------------	------------------------------------

Note: When used for interior purposes, PVB Varnish series 0208 adheres on aluminium and galvanized steel. PVB paint does not provide long term protection against corrosion. Waterborne Polyurethane Varnish series 0571 is our water-borne alternative.

This information is based on our present state of knowledge and is intended to provide general notes on our products and their use. It should not, therefore, be construed as guaranteeing specific properties of the product described or its suitability for a particular application. The quality of our products is guaranteed under our General Conditions of Sale.

EFApaint A/S, Energivej 13, DK-6700 Esbjerg

TLF. +45 75 12 86 00 e-mail: info@efapaint.dk

www.efapaint.dk