

TECHNICAL DATA SHEET

en

Name of product:

FAXE Special Lye THIX 0229

Type of product: Lye based on Sodium hydroxide.

Application: FAXE Special Lye is used on untreated oak, where a special surface is wanted. FAXE Special Lye THIX gives a characteristic aged and smoked look on oak.

Properties: FAXE Special Lye THIX gives patina and an aged (smoked) look on oak. Depending upon the type of wood, the heartwood will be accentuated. The treatment has a good color stability.

Solids: 7 weight % 7 vol. %

Pre-treatment: The wood has to be sanded, clean and dry.

Application:

Method:

Industrial roller coater

Recommended viscosity:

No thinning required

Thinner:

Drying:

	Drying time	Film thickness - dry
Dry to use	5 hours 20 °C	15 - 30 gram / m ²

System Specification:

Application:

1x FAXE Special Lye THIX with a moss rubber roller
1 x brushing (while the lye is wet).

Drying

After Care:

1x FAXE HS Industry Oil or 1x FAXE Oxi. Industryoil

Aftercare: Dust and loose dirt can be removed with a brush or vacuum cleaner. We recommend FAXE Active Care or FAXE Wooden Floor Soap for cleaning. To renovate, clean the surface with FAXE Intensive Cleaner and then apply a coat of FAXE Woodcare Oil or another FAXE Oil.

Coverage: Theoretical: 10 m²/ltr.

Storage: Frostfree, cool, and closed.

Shelf-life: 12 Months in an unopened container

Cleaning: The tools should be cleaned with water.

This information is based on our present state of knowledge and is intended to provide general notes on our products and their use. It should not, therefore, be construed as guaranteeing specific properties of the product described or its suitability for a particular application. The quality of our products is guaranteed under our General Conditions of Sale.

EFApaint A/S, Energivej 13, DK-6700 Esbjerg

TLF. +45 75 12 86 00

e-mail: info@efapaint.dk

www.efapaint.dk