

TECHNICAL DATA SHEET

en

Name of product:

FAXE Universal Lye THIX 0251

Type of product:	White lye based on vegetable oils, naturel wax, pigments and sodium hydroxide.	
Application:	FAXE Universal Lye THIX, is a lye, which slows down the yellowing process of wood in a chemical way.	
Properties:	Lye slows down the yellowing process - can be applied to roller and spray equipment.	
Solids:	8 weight %	8 vol. %
Pre-treatment:	The wood has to be sanded, clean and dry.	

Application:

Method:	Recommended viscosity:	Thinner:
Industrial roller coater	No thinning required	-
Spraying	No thinning required	-

FAXE Universal Lye THIX is made thixotropic so that it can be applied to the roller and spray equipment in the industry.

Drying:

	Drying time	Film thickness - dry
Dry to touch	5 hours 20 °C	20 - 25 gram / m ²
Forced drying	5 minutes 40 °C	20 - 25 gram / m ²

System Specification:

1x FAXE Universal Lye THIX
The product has to be stirred before and during use.

After Care:

Subsequently, the surface can be treated with oil, hardwax, Invisioil and the like, depending on the surface and the effect you want.

Aftercare: Dust and loose dirt can be removed with a brush or vacuum cleaner. We recommend FAXE Active Care or FAXE Wooden Floor Soap for cleaning. To renovate, clean the surface with FAXE Intensive Cleaner and then apply a coat of FAXE Woodcare Oil or another FAXE Oil.

Coverage:	Theoretical: 10 m ² /ltr.
Storage:	Store above 5° C.
Shelf-life:	12 Months in an unopened container
Cleaning:	The tools should be cleaned with water.

This information is based on our present state of knowledge and is intended to provide general notes on our products and their use. It should not, therefore, be construed as guaranteeing specific properties of the product described or its suitability for a particular application. The quality of our products is guaranteed under our General Conditions of Sale.

EFApaint A/S, Energivej 13, DK-6700 Esbjerg

TLF. +45 75 12 86 00 e-mail: info@efapaint.dk

www.efapaint.dk